

www.raybonecork.com



Black EVA Rubber Pads With Adhesive

As one standard packing materials for glass factories, "Raybone" Black EVA Rubber Pads With Adhesive, has competitive price advantage and cover most of the European and American markets for glass industry. "Raybone" is a large-scale Eva Rubber Pads manufacturer and supplier in China, who specialized in Eva Rubber Pads for about 20 years. Hope your contact as our agents/distributors all over the world for the mutual benefits from the

long-term cooperation.

Product Description

China Quality Black EVA Rubber Pads with Adhesive Manufacturers and Suppliers "Raybone" is famous in China glass market. Glass, windows, doors and mirrors are fragile. "Raybone" Black EVA Rubber Pads with Adhesive are easy to be removed cleanly, yet adhered securely to architectural glass, auto glass, furniture glass, stone, windows & doors, during transporting, packing, storage and installation. Setting between the glass, the pads can absorb vibration, maintain position and prevent breakage.

Black Eva Rubber Pads With Adhesive Parameter (Specification)					
MODEL NO.	SIZE	THICKNESS	PADS/BOX	VOL.(cbm)	GW(kg)
SC-2040	20mm*20mm	4mm EVA	20000	0.045	10



Black Eva Rubber Pads With Adhesive Feature And Application

Features: 1. Strong Stickiness 2. High Temperature Resistance, Stable Performance, Temperature Resistance Up To 70~9 Degrees 3. Waterproof, Moisture-Proof 4. Good Flexibility, Shockproof, Anti-Skid, Compression Resistance 5. No Sawdust, Clean And No



Residue

Using for:Architectural Glass, Auto Glass, Furniture glass, Windows & Doors, etc Application In The Glass Deep-Processing Industry: Transporting, Packing, Storage, Installation,Etc

Application Method: Put The Black Eva Rubber Pads With Adhesive On The Edge Of The Glass, The Distance Between Two Pads Is About 30-40Cm, Totally 8 Pads On The Area Of 1 Square Meter



Black Eva Rubber Pads With Adhesive Details

Black Eva Rubber Pads With Adhesive Are Machined From Black Eva Rubber. The Conventional Thickness Of Eva Rubber Pad Is 2Mm~5Mm. The Hardness Of Conventional Specifications Is About 60 Degrees, And Materials With Different Hardness Such As 38 Degrees, 70 Degrees, And 80 Degrees Are Available. In Addition To Regular Thickness And Hardness, Other Thickness, Hardness And Size Can Be Customized According To Customer Needs.